

SIDE ENTRY SMT JACK DEC TYPE



7660 SERIES. Right angle PCB jack.


General Features

- Available in 8/8 circuits
- Standard telephone jack FCC-68
- Low profile: 10.90 mm.
- Accept standard plugs FCC-68 type
- Selective gold plating with different finish
- Plastic foot print

Materials

- Insulator: Thermoplastic UL 94V-0
- Contact: 0.35 mm thickness phosphor bronze
- Operating temperature. -25°C to + 85°C
- RoHS compliant

Dimensional Information




Electrical Features

- Voltage rating: < 125V
- Current rating: < 1.50 A
- Contact resistance: < 20 mΩ
- Dielectric withstanding voltage: 300 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Durability: 1000 cycles



Ordering Information:

7660 - T - XX - 1 - E
1 2 3 4

1. Connector Series

2. (T) Contact Plating

- T = 4. 6μ" gold over 50μ" nickel
- T = 5. 15μ" gold over 50μ" nickel
- T = 6. 30μ" gold over 50μ" nickel
- T = 7. 50μ" gold over 50μ" nickel

3. (XX) Circuit Size

- Available in 8/8 circuits

4. (E)Packing Options

- E = 2. REEL + TUBE